
PANEL DESIGNS





Black Article no. 350125121503 Width: 600 mm Hight: 2.400 mm Thickness: 21 mm



Grey
Article no. 350125121504
Width: 600 mm
Hight: 2.400 mm
Thickness: 21 mm



Walnut
Article no. 350125121506
Width: 600 mm
Hight: 2.400 mm
Thickness: 21 mm



Light
Article no. 350125121501
Width: 600 mm
Hight: 2.400 mm
Thickness: 21 mm



Oiled Article no. 350125121502 Width: 600 mm Hight: 2.400 mm Thickness: 21 mm



Smoked Article no. 350125121505 Width: 600 mm Hight: 2.400 mm Thickness: 21 mm

vanDockum acoustic panels are specially designed and built in our own factories in Denmark.

The particularly hygienic surfaces are allergy-friendly and easy to clean. The surfaces are UV colour-stable, which makes them the market's most unique and easy-to-clean acoustic panel.

Acoustic panels are made in standard width 600 x height 2400/2440 mm.

Slats are 25 mm wide and 12 mm deep. The distance between slats is 15 mm. Acoustic slats are made with a soft rounded edge to give the panel a soft organic look.

The sound absorber is made of 100% polyester, which is 100% recyclable. The sound absorber is available in 3 colors from light grey, medium gray and dark grey.

Polyester and sound absorber are built at a factory in the Nordics.

All materials for vanDockum acoustic panels come from selected Nordic manufacturers and suppliers with the highest focus on protecting the environment as much as possible.

Acoustic panels can be packed on pallets with 50 pieces, for the greatest possible reduction of CO2 load, environmental considerations and own requirements for sustainability.

Credited Sound absorbing rapport according to ISO DS/EN 354:2003 are made by DELTA in Hørsholm, a Part of FORCE Technology.

WOOD SE DIY









Light

















WOOD







Grey



Walnut



Light



Oiled



Smoked

WOOD SP DIY




Black



Grey



Walnut



Light



Oiled



Smoked